

Product info sheet:
glimtrex[®] WPC-Impregnator



Product description

glimtrex[®] WPC-Impregnator for a weather- and UV-resistant coating of WPC (Wood Plastic Composites) such as Resysta- and Poly rattan surfaces.

glimtrex[®] WPC-Impregnator is solvent-free, colourless and made from natural high quality oils. The material is open-pored.

Application Instructions

- WPC surfaces can react differently to the product, so we recommend to do sample
- the surface has to be frost-free, clean, dust free and dry. Therefore we recommend WPC-Cleaner, which removes algae, grime and dirt highly effectively.
- apply glimtrex[®] WPC-Impregnator twice with a brush, a roller or a cloth (intermediate drying approx. 12 hours)
- processing temperature (incl. drying) should be above +8° C
- stir the product before using it
- recoating after approx. 8-12 hours
- wet and cold weather can extend the drying process

Yield

1 litre for 20 m². Depending on the structure of the surface. If the surface is rippled the yield is higher.

Cleaning

Clean the equipment directly after using them with water and soap.



Technical information

Available in 0.75 litre and 2.5 litre tins.

Store cold but frost-free. The shelf life is 3 years in the closed original tin. Decant the open tins and hermetically seal them. Use them prompt.

Important tips:

Keep away from children. Can evoke an allergic reaction. Dried material left over can be disposed in the household waste.

Please look at the current safety data sheets. You will find them at www.glimtrex.de/downloads.

This information is purely advisory and is based on the best knowledge available through careful research. This information cannot be held as legally binding.