

Trade name: glimtrex SIGNUM 1-Pack Lacquer mat 103003

Version: 34 / DE

Revision: 31.07.2020

Replaces Version: 33 / DE

Print date: 04.02.21

## 1. Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

glimtrex SIGNUM 1-Pack Lacquer mat 103003

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/preparation

Surface treatment of wood and other materials

#### Identified Uses

	-----
SU22	REACHSET 2003 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix
PROC10	Roller application or brushing
	-----

	-----
SU21	REACHSET 3003 Consumer uses: Private households (= general public = consumers)
ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix
PROC10	Roller application or brushing

### 1.3. Details of the supplier of the safety data sheet

#### Manufacturer

glimtrex GmbH  
Orkotten 68  
48291 Telgte  
Telephone no. +49 (0) 2504 88887-111  
Fax no. +49 (0) 2504 88887-112  
E-mail address info@glimtrex.de

### 1.4. Emergency telephone number

Germany: +49 (0) 30 30668700

## 2. Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification (Regulation (EC) No. 1272/2008)

This product is not classified hazardous in accordance with Regulation (EC) No 1272/2008.

### 2.2. Label elements

#### Labelling according to regulation (EC) No 1272/2008

EUH208 Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3- one [EC no. 220-239-6] (3:1); reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3- one [EC no. 220-239-6] (3:1), 2,4,7,9-tetramethyldec-5-yne-4,7-diol, May produce an allergic reaction.

Trade name: glimtrex SIGNUM 1-Pack Lacquer mat 103003

Version: 34 / DE

Revision: 31.07.2020

Replaces Version: 33 / DE

Print date: 04.02.21

**Supplemental information**

EUH210

Safety data sheet available on request.

**2.3. Other hazards**

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB) (if not listed in Section 3).

**3. Composition/information on ingredients****Hazardous ingredients****2-(2-butoxyethoxy)ethanol**

CAS No.	112-34-5			
EINECS no.	203-961-6			
Registration no.	01-2119475104-44			
Concentration	>= 1	<	5	%
Classification (Regulation (EC) No. 1272/2008)	Eye Irrit. 2		H319	

**2-butoxyethanol**

CAS No.	111-76-2			
EINECS no.	203-905-0			
Registration no.	01-2119475108-36			
Concentration	>= 1	<	4	%
Classification (Regulation (EC) No. 1272/2008)	Acute Tox. 4		H302	Route of exposure: Oral exposure
	Acute Tox. 4		H312	Route of exposure: Dermal exposure
	Acute Tox. 4		H332	Route of exposure: Inhalation exposure
	Eye Irrit. 2		H319	
	Skin Irrit. 2		H315	

**2,4,7,9-tetramethyldec-5-yne-4,7-diol**

CAS No.	126-86-3			
EINECS no.	204-809-1			
Registration no.	01-2119954390-39			
Concentration	>= 0,1	<	1	%
Classification (Regulation (EC) No. 1272/2008)	Eye Dam. 1		H318	
	Skin Sens. 1B		H317	
	Aquatic Chronic 3		H412	

**2-dimethylaminoethanol**

CAS No.	108-01-0			
EINECS no.	203-542-8			
Registration no.	01-2119492298-24			
Concentration	>= 0,1	<	1	%
Classification (Regulation (EC) No. 1272/2008)	Flam. Liq. 3		H226	
	Acute Tox. 3		H331	Route of exposure: Inhalation exposure
	Acute Tox. 4		H312	Route of exposure: Dermal exposure

Trade name: glimtrex SIGNUM 1-Pack Lacquer mat 103003

Version: 34 / DE

Revision: 31.07.2020

Replaces Version: 33 / DE

Print date: 04.02.21

Acute Tox. 4	H302	Route of exposure: Oral exposure
Skin Corr. 1B	H314	
STOT SE 3	H335	Respiratory tract

Concentration limits (Regulation (EC) No. 1272/2008)  
 STOT SE 3 H335 >= 5

**1,2-benzisothiazol-3(2H)-one**

CAS No. 2634-33-5  
 EINECS no. 220-120-9  
 Concentration < 0,05 %  
 Classification (Regulation (EC) No. 1272/2008)

Acute Tox. 4	H302
Skin Irrit. 2	H315
Eye Dam. 1	H318
Skin Sens. 1	H317
Aquatic Acute 1	H400
Aquatic Chronic 2	H411

Concentration limits (Regulation (EC) No. 1272/2008)  
 Skin Sens. 1 H317 >= 0,05 %

**reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H - isothiazol-3- one [EC no. 220-239-6] (3:1); reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3- one [EC no. 220-239-6] (3:1)**

CAS No. 55965-84-9  
 EINECS no. 247-500-7  
 Concentration < 0,001 %  
 Classification (Regulation (EC) No. 1272/2008)

Acute Tox. 2	H330
Acute Tox. 2	H310
Acute Tox. 3	H301
Skin Corr. 1B	H314
Skin Sens. 1	H317
Aquatic Acute 1	H400
Aquatic Chronic 1	H410
Eye Dam. 1	H318

Concentration limits (Regulation (EC) No. 1272/2008)

Skin Corr. 1C	H314	>= 0,6 %
Skin Irrit. 2	H315	>= 0,06 %
Eye Irrit. 2	H319	>= 0,06 %
Skin Sens. 1	H317	>= 0,0015 %
Eye Dam. 1	H318	>= 0,6 %
Aquatic Chronic 1	H410	M = 100
1		
Aquatic Acute 1	H400	M = 100

**Further ingredients****2-(2-ethoxyethoxy)ethanol**

CAS No. 111-90-0  
 EINECS no. 203-919-7  
 Registration no. 01-2119475105-42  
 Concentration >= 1 < 10 %  
 Advice: [3]

Trade name: glimtrex SIGNUM 1-Pack Lacquer mat 103003

Version: 34 / DE

Revision: 31.07.2020

Replaces Version: 33 / DE

Print date: 04.02.21

**Note**

[3] Substance with occupational exposure limits

**4. First aid measures**

**4.1. Description of first aid measures**

**General information**

Remove affected person from danger area, lay him down. In all cases of doubt, or when symptoms persist, seek medical attention. Get medical advice/attention if you feel unwell. First aider: Pay attention to self-protection!

**After inhalation**

When spray fog inhaled, seek medical aid.

**After skin contact**

Wash off immediately with soap and water. Do NOT use solvents or thinners. Consult a doctor if skin irritation persists.

**After eye contact**

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. Take medical treatment.

**After ingestion**

Do not induce vomiting. Take medical treatment.

**4.2. Most important symptoms and effects, both acute and delayed**

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

**4.3. Indication of any immediate medical attention and special treatment needed**

**Hints for the physician / treatment**

Treat symptomatically.

**5. Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

Recommended: alcohol resistant foam, CO<sub>2</sub>, powders, water spray/mist

**Non suitable extinguishing media**

Do not use a solid water stream as it may scatter and spread fire.

**5.2. Special hazards arising from the substance or mixture**

Fire will produce dense black smoke. In a fire, hazardous decomposition products may be produced. Exposure to decomposition products may cause a health hazard.

**5.3. Advice for firefighters**

**Special protective equipment for fire-fighting**

In case of combustion evolution of dangerous gases possible. Use self-contained breathing apparatus.

**Other information**

Do not allow run-off from fire fighting to enter drains or water courses. Cool closed containers exposed to fire with water. Standard procedure for chemical fires.

Trade name: glimtrex SIGNUM 1-Pack Lacquer mat 103003

Version: 34 / DE

Revision: 31.07.2020

Replaces Version: 33 / DE

Print date: 04.02.21

## 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Do not inhale vapours. Do not inhale gases. Do not inhale mist.

### 6.2. Environmental precautions

Do not allow to enter drains or waterways. Do not allow to enter soil, waterways or waste water canal. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

### 6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Do NOT use solvents or thinners. Send in suitable containers for recovery or disposal.

### 6.4. Reference to other sections

Refer to protective measures listed in Sections 7 and 8.

## 7. Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Keep container tightly closed and dry in a cool, well-ventilated place. Avoid contact with skin and eyes. Avoid inhalation of vapour and spray mist. Do not eat, drink or smoke when using this product. Use personal protective clothing. For personal protection see Section 8.

#### Advice on protection against fire and explosion

Fight fire with normal precautions from a reasonable distance.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep only in the original container in a cool, well ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

#### Hints on storage assembly

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

#### Storage classes

Storage class according to TRGS 510      10      Flammable liquids

#### Further information on storage conditions

Keep away from heat. Protect from sunlight. Keep away from sources of ignition - No smoking. Store in accordance with the particular national regulations.

## 8. Exposure controls/personal protection

### 8.1. Control parameters

#### Other information

-

#### Derived No/Minimal Effect Levels (DNEL/DMEL)

##### 2-butoxyethanol

Type of value

Derived No Effect Level (DNEL)

Reference group

Workers (professional)

Trade name: glimtrex SIGNUM 1-Pack Lacquer mat 103003

Version: 34 / DE

Revision: 31.07.2020

Replaces Version: 33 / DE

Print date: 04.02.21

Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Acute effects	
Concentration	89	mg/kg
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	246	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	75	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	20	ppm
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	89	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	246	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	1091	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	3,2	mg/kg/d

Trade name: glimtrex SIGNUM 1-Pack Lacquer mat 103003

Version: 34 / DE

Revision: 31.07.2020

Replaces Version: 33 / DE

Print date: 04.02.21

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	13,4	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	123	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Acute effects	
Concentration	44,5	mg/kg
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Acute effects	
Concentration	426	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	6,3	mg/kg
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	106,4	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	38	mg/kg
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	

Trade name: glimtrex SIGNUM 1-Pack Lacquer mat 103003

Version: 34 / DE

Revision: 31.07.2020

Replaces Version: 33 / DE

Print date: 04.02.21

Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	59	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	49	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	26,7	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	135	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	147	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	89	mg/kg/d
<b>2-(2-ethoxyethoxy)ethanol</b>		
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	50	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	37	mg/m <sup>3</sup>



Trade name: glimtrex SIGNUM 1-Pack Lacquer mat 103003

Version: 34 / DE

Revision: 31.07.2020

Replaces Version: 33 / DE

Print date: 04.02.21

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	18	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	25	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	18,3	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	25	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	9	mg/m <sup>3</sup>
<b>2-(2-butoxyethoxy)ethanol</b>		
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	14	ppm
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	20	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	

Trade name: glimtrex SIGNUM 1-Pack Lacquer mat 103003

Version: 34 / DE

Revision: 31.07.2020

Replaces Version: 33 / DE

Print date: 04.02.21

Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	10	ppm
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	10	ppm
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	7,5	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	10	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	5	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	1,3	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	5	mg/m <sup>3</sup>
<b>2-dimethylaminoethanol</b>		
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	

Trade name: glimtrex SIGNUM 1-Pack Lacquer mat 103003

Version: 34 / DE

Revision: 31.07.2020

Replaces Version: 33 / DE

Print date: 04.02.21

Concentration 1,04 mg/kg

Type of value Derived No Effect Level (DNEL)

Reference group Workers (professional)

Duration of exposure Long-term

Route of exposure inhalative

Mode of action Systemic effects

Concentration 7,4 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Long-term

Route of exposure inhalative

Mode of action Systemic effects

Concentration 2,2 mg/m<sup>3</sup>

**Predicted No Effect Concentration (PNEC)**

**2-butoxyethanol**

Type of value PNEC

Type Freshwater

Concentration 8,8 mg/l

Type of value PNEC

Type Saltwater

Concentration 0,88 mg/l

Type of value PNEC

Type saltwater sediment

Concentration 3,46 mg/kg

Type of value PNEC

Type Sewage treatment plant (STP)

Concentration 463 mg/l

Type of value PNEC

Type Soil

Concentration 2,33 mg/kg

**2-(2-ethoxyethoxy)ethanol**

Type of value PNEC

Type Freshwater

Concentration 0,74 mg/l

Type of value PNEC

Type marine water

Concentration 0,074 mg/l

Type of value PNEC

Type Sewage treatment plant (STP)

Concentration 500 mg/l

Type of value PNEC

Trade name: glimtrex SIGNUM 1-Pack Lacquer mat 103003

Version: 34 / DE

Revision: 31.07.2020

Replaces Version: 33 / DE

Print date: 04.02.21

Type	Fresh water sediment	
Concentration	2,74	mg/kg
Type of value	PNEC	
Type	saltwater sediment	
Concentration	274	mg/kg
Type of value	PNEC	
Type	Soil	
Concentration	0,15	mg/kg

**2-(2-butoxyethoxy)ethanol**

Type of value	PNEC	
Type	Freshwater	
Concentration	1	mg/l
Type of value	PNEC	
Type	marine water	
Concentration	0,1	mg/l
Type of value	PNEC	
Type	Fresh water sediment	
Concentration	4	mg/kg
Type of value	PNEC	
Type	saltwater sediment	
Concentration	0,4	mg/kg
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	200	mg/l
Type of value	PNEC	
Type	Soil	
Concentration	0,4	mg/l

**2-dimethylaminoethanol**

Type of value	PNEC	
Type	Freshwater	
Concentration	0,0661	mg/l
Type of value	PNEC	
Type	Saltwater	
Concentration	0,00661	mg/l
Type of value	PNEC	
Conditions	sporadic release	
Concentration	0,0661	mg/l
Type of value	PNEC	
Type	Fresh water sediment	
Concentration	0,0529	mg/kg

Trade name: glimtrex SIGNUM 1-Pack Lacquer mat 103003

Version: 34 / DE

Revision: 31.07.2020

Replaces Version: 33 / DE

Print date: 04.02.21

Type of value	PNEC		
Type	Soil		
Concentration	0,0177		mg/kg
Type of value	PNEC		
Type	Sewage treatment plant (STP)		
Concentration	10		mg/l

## 8.2. Exposure controls

### Exposure controls

Users are advised to consider national Occupational Exposure Limits or other equivalent values. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

### Respiratory protection

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol. Recommended Filter type: Respiratory protection mask with combination filter A/P2

### Hand protection

Protective gloves complying with EN 374.

Glove material

Appropriate Material butyl-rubber

Material thickness  $\geq$  0,5 mm

Breakthrough time  $\geq$  120 min

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

### Eye protection

Wear eye glasses with side protection according to EN 166.

### Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

## 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Form	liquid
Colour	white
Odour	characteristic
Odour threshold	
Remarks	not determined
pH value	

Trade name: glimtrex SIGNUM 1-Pack Lacquer mat 103003

Version: 34 / DE

Revision: 31.07.2020

Replaces Version: 33 / DE

Print date: 04.02.21

Value 8  
Concentration/H<sub>2</sub>O 100

**Melting point**

Remarks not determined

**Freezing point**

Remarks not determined

**Initial boiling point and boiling range**

Remarks not determined

**Flash point**

Value > 60 °C

**Flammability (solid, gas)**

not determined

**Upper/lower flammability or explosive limits**

Remarks not determined

**Vapour pressure**

Remarks not determined

**Vapour density**

Remarks not determined

**Density**

Value appr. 1,045 kg/l  
Temperature 20 °C

**Solubility in water**

Remarks not determined

**Solubility(ies)**

Remarks not determined

**Partition coefficient: n-octanol/water**

Remarks not determined

**Ignition temperature**

Remarks not determined

**Decomposition temperature**

Remarks not determined

**Viscosity**

Remarks not determined

**Efflux time**

Value 40 to 60 s  
Temperature 20 °C  
Method DIN EN ISO 2431 - 4 mm

**Explosive properties**

evaluation not determined

**Oxidising properties**

Remarks not determined

**9.2. Other information**

Trade name: glimtrex SIGNUM 1-Pack Lacquer mat 103003

Version: 34 / DE

Revision: 31.07.2020

Replaces Version: 33 / DE

Print date: 04.02.21

**Non-volatile content**

Value	35,3	%
Method	calculated value	

**10. Stability and reactivity****10.1. Reactivity**

Stable under recommended storage and handling conditions (see section 7).

**10.2. Chemical stability**

Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

To avoid thermal decomposition, do not overheat.

**10.4. Conditions to avoid**

Isolate from sources of heat, sparks and open flame.

**10.5. Incompatible materials**

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

**10.6. Hazardous decomposition products**Carbon monoxide and carbon dioxide, nitrous oxides (NO<sub>x</sub>), dense black smoke, No decomposition if used as prescribed.**11. Toxicological information****11.1. Information on toxicological effects****Acute oral toxicity**

ATE	> 10.000	mg/kg
Method	calculated value (Regulation (EC) No. 1272/2008)	
Remarks	Based on available data, the classification criteria are not met.	

**Acute oral toxicity (Components)****2-butoxyethanol**

Species	guinea pig	
LD50	1414	mg/kg
Method	OECD 401	
Source	1 (reliable without restriction)	

**2-dimethylaminoethanol**

Species	rat	
LD50	1183	mg/kg
Method	OECD 401	

**1,2-benzisothiazol-3(2H)-one**

Species	rat	
LD50	1193	mg/kg

**reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H - isothiazol-3- one [EC no. 220-239-6] (3:1); reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3- one [EC no. 220-239-6] (3:1)**

ATE	100	mg/kg
Method	conversion value	

Trade name: glimtrex SIGNUM 1-Pack Lacquer mat 103003

Version: 34 / DE

Revision: 31.07.2020

Replaces Version: 33 / DE

Print date: 04.02.21

**Acute dermal toxicity**

ATE	>	10.000	mg/kg
Method	calculated value (Regulation (EC) No. 1272/2008)		
Remarks	Based on available data, the classification criteria are not met.		

**Acute dermal toxicity (Components)****2-butoxyethanol**

Species	guinea pig		
LD50	435		mg/kg
Source	1 (reliable without restriction)		

**2-dimethylaminoethanol**

Species	rabbit		
LD50	1219		mg/kg

**reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H - isothiazol-3- one [EC no. 220-239-6] (3:1); reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3- one [EC no. 220-239-6] (3:1)**

ATE	50		mg/kg
Method	conversion		

**Acute inhalational toxicity**

ATE	>	20	mg/l
Administration/Form	Dust/Mist		
Method	calculated value (Regulation (EC) No. 1272/2008)		
Remarks	Based on available data, the classification criteria are not met.		

**Acute inhalative toxicity (Components)****2-butoxyethanol**

Species	rat		
LC50	2,56		mg/l
Duration of exposure	4	h	
Administration/Form	Dust/Mist		
Source	1 (reliable without restriction)		

**2-dimethylaminoethanol**

Species	rat		
LC50	0,5		mg/l
Duration of exposure	4	h	
Administration/Form	Dust/Mist		
Method	conversion value		

**reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H - isothiazol-3- one [EC no. 220-239-6] (3:1); reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3- one [EC no. 220-239-6] (3:1)**

ATE	0,05		mg/l
Duration of exposure	4	h	
Administration/Form	Dust/Mist		
Method	conversion value		
Remarks	Mist		

**Skin corrosion/irritation**

Method	Calculation method (Regulation (EC) No. 1272/2008)		
Remarks	Based on available data, the classification criteria are not met.		

**Skin corrosion/irritation (Components)****2-butoxyethanol**



Trade name: glimtrex SIGNUM 1-Pack Lacquer mat 103003

Version: 34 / DE

Revision: 31.07.2020

Replaces Version: 33 / DE

Print date: 04.02.21

Species	rabbit
Duration of exposure	4 h
Observation Period	28 d
evaluation	Irritating to skin and mucous membranes
Method	EEC 84/449, B.4

**2-dimethylaminoethanol**

Species	rabbit
---------	--------

**1,2-benzisothiazol-3(2H)-one**

evaluation	Irritating to skin.
------------	---------------------

**reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H - isothiazol-3- one [EC no. 220-239-6] (3:1); reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3- one [EC no. 220-239-6] (3:1)**

Species	rabbit
evaluation	Severe skin irritation

**Serious eye damage/irritation**

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

**Serious eye damage/irritation (Components)****2-butoxyethanol**

Species	rabbit
Duration of exposure	24 h
Observation Period	21 d
evaluation	Eye irritation
Source	1 (reliable without restriction)

**2-(2-butoxyethoxy)ethanol**

Species	rabbit
evaluation	Irritating to eyes.
Source	2 (reliable with restrictions)

**2-dimethylaminoethanol****1,2-benzisothiazol-3(2H)-one**

evaluation	Irritating to eyes.
------------	---------------------

**2,4,7,9-tetramethyldec-5-yne-4,7-diol****Sensitization**

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

**Sensitization (Components)****1,2-benzisothiazol-3(2H)-one**

Reference substance	1,2-benzisothiazol-3(2H)-one
evaluation	May cause sensitization by skin contact.

**reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H - isothiazol-3- one [EC no. 220-239-6] (3:1); reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3- one [EC no. 220-239-6] (3:1)**

Species	guinea pig
evaluation	Causes sensitisation on guinea-pigs.

**2,4,7,9-tetramethyldec-5-yne-4,7-diol**

evaluation	May cause sensitization by skin contact.
------------	--

**Mutagenicity**

Method	Calculation method (Regulation (EC) No. 1272/2008)
--------	--

Trade name: glimtrex SIGNUM 1-Pack Lacquer mat 103003

Version: 34 / DE

Revision: 31.07.2020

Replaces Version: 33 / DE

Print date: 04.02.21

Remarks Based on available data, the classification criteria are not met.

**Reproductive toxicity**

Method Calculation method (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

**Carcinogenicity**

Method Calculation method (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity (STOT)****Single exposure**

Method Calculation method (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

**Repeated exposure**

Remarks Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity (STOT) (Components)****2-dimethylaminoethanol****Specific target organ toxicity - single exposure**

evaluation May cause respiratory irritation.

Route of exposure inhalative

Organs: Respiratory tract

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Other information**

No toxicological data are available.

**12. Ecological information****12.1. Toxicity****General information**

For this subsection there is no ecotoxicological data available on the product as such.

**Fish toxicity (Components)****2-(2-ethoxyethoxy)ethanol**

Species Spotted catfish  
LC50 6010 mg/l

Duration of exposure 96 h

**1,2-benzisothiazol-3(2H)-one**

Species Oncorhynchus mykiss (rainbow trout)  
LC50 2,18 mg/l

Duration of exposure 96 h

**reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H - isothiazol-3- one [EC no. 220-239-6] (3:1); reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3- one [EC no. 220-239-6] (3:1)**

Species Oncorhynchus mykiss (rainbow trout)  
LC50 0,19 mg/l

Duration of exposure 96 h

**Daphnia toxicity (Components)****1,2-benzisothiazol-3(2H)-one**

Trade name: glimtrex SIGNUM 1-Pack Lacquer mat 103003

Version: 34 / DE

Revision: 31.07.2020

Replaces Version: 33 / DE

Print date: 04.02.21

Species	Daphnia magna (Water flea)	
EC50	2,94	mg/l
Duration of exposure	48	h

**reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H - isothiazol-3- one [EC no. 220-239-6] (3:1); reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3- one [EC no. 220-239-6] (3:1)**

Species	Daphnia magna (Water flea)	
EC50	0,16	mg/l
Duration of exposure	48	h

**2,4,7,9-tetramethyldec-5-yne-4,7-diol**

Species	Daphnia magna (Water flea)	
EC50	91	mg/l
Duration of exposure	48	h

**Algae toxicity (Components)**

**reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H - isothiazol-3- one [EC no. 220-239-6] (3:1); reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3- one [EC no. 220-239-6] (3:1)**

Species	Scenedesmus capricornutum (fresh water algae)	
EC50	0,018	mg/l
Duration of exposure	72	h

**Bacteria toxicity (Components)**

**reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H - isothiazol-3- one [EC no. 220-239-6] (3:1); reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3- one [EC no. 220-239-6] (3:1)**

Species	activated sludge	
EC50	4,5	mg/l

**12.2. Persistence and degradability****General information**

For this subsection there is no ecotoxicological data available on the product as such.

**Biodegradability (Components)****1,2-benzisothiazol-3(2H)-one**

evaluation Readily biodegradable.

**reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H - isothiazol-3- one [EC no. 220-239-6] (3:1); reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3- one [EC no. 220-239-6] (3:1)**

evaluation Not readily biodegradable.

**12.3. Bioaccumulative potential****General information**

For this subsection there is no ecotoxicological data available on the product as such.

**Partition coefficient: n-octanol/water**

Remarks not determined

**12.4. Mobility in soil****General information**

For this subsection there is no ecotoxicological data available on the product as such.

**Mobility in soil**



Trade name: glimtrex SIGNUM 1-Pack Lacquer mat 103003

Version: 34 / DE

Revision: 31.07.2020

Replaces Version: 33 / DE

Print date: 04.02.21

no data available

**12.5. Results of PBT and vPvB assessment**

**General information**

For this subsection there is no ecotoxicological data available on the product as such.

**12.6. Other adverse effects**

**General information**

For this subsection there is no ecotoxicological data available on the product as such.

**13. Disposal considerations**

**13.1. Waste treatment methods**

**Disposal recommendations for the product**

EWC waste code 080111 - waste paint and varnish containing organic solvents or other dangerous substances

EWC waste code 200127 - paint, inks, adhesives and resins containing dangerous substances

Where possible recycling is preferred to disposal or incineration.

Do not allow to enter drains or waterways.

**modified product**

EWC waste code 080115 - aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances

**Dried residues**

EWC waste code 080112 - waste lacquers and waste paint except those falling under 080111

**Disposal recommendations for packaging**

EWC waste code 150110 - packaging containing residues of or contaminated by dangerous substances

Germany: KBS system for sheet covering

Completely emptied packagings can be given for recycling.

**14. Transport information**

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
<b>14.1. UN number</b>	Not classified as dangerous in the meaning of transport regulations.	Not classified as dangerous in the meaning of sea and air transport regulations.	Not a dangerous substance as defined in the above regulations.

**15. Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Water Hazard Class (Germany)**

Water Hazard Class (Germany) WGK 2

Remarks Derivation of WGK according to Annex 1 No. 5.2 AwSV

Trade name: glimtrex SIGNUM 1-Pack Lacquer mat 103003

Version: 34 / DE

Revision: 31.07.2020

Replaces Version: 33 / DE

Print date: 04.02.21

**VOC**

VOC (EU)	7,3	%	76	g/l
----------	-----	---	----	-----

**16. Other information****Hazard statements listed in Chapter 3**

H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

**CLP categories listed in Chapter 3**

Acute Tox. 2	Acute toxicity, Category 2
Acute Tox. 3	Acute toxicity, Category 3
Acute Tox. 4	Acute toxicity, Category 4
Aquatic Acute 1	Hazardous to the aquatic environment, acute, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic, Category 3
Eye Dam. 1	Serious eye damage, Category 1
Eye Irrit. 2	Eye irritation, Category 2
Flam. Liq. 3	Flammable liquid, Category 3
Skin Corr. 1B	Skin corrosion, Category 1B
Skin Irrit. 2	Skin irritation, Category 2
Skin Sens. 1	Skin sensitization, Category 1
Skin Sens. 1B	Skin sensitization, Category 1B
STOT SE 3	Specific target organ toxicity - single exposure, Category 3

**Abbreviations**

ADR - Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 RID - Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
 IMDG - International Maritime Code for Dangerous Goods  
 IATA - International Air Transport Association  
 IATA-DGR - Dangerous Goods Regulations by the "International Air Transport Association" (IATA)  
 ICAO-TI - Technical Instructions by the "International Civil Aviation Organization" (ICAO)  
 GHS - Globally Harmonized System of Classification and Labelling of Chemicals  
 EINECS - European Inventory of Existing Commercial Chemical Substances  
 CAS - Chemical Abstracts Service (division of the American Chemical Society)

Trade name: glimtrex SIGNUM 1-Pack Lacquer mat 103003

Version: 34 / DE

Revision: 31.07.2020

Replaces Version: 33 / DE

Print date: 04.02.21

GefStoffV - Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

LOAEL - Lowest Observed Adverse Effect Level

LOEL - Lowest Observed Effect Level

NOAEL - No Observed Adverse Effect Level

NOEC - No Observed Effect Concentration

NOEL - No Observed Effect Level

OECD - Organisation for Economic Cooperation and Development

VOC - Volatile Organic Compounds

Changes since the last version are highlighted in the margin (\*\*\*) . This version replaces all previous versions.

This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification.

The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

The information contained herein is based on the present state of our knowledge and does therefore not guarantee certain properties.

## **Annex to the extended Safety Data Sheet (eSDS)**

### **Short title of the exposure scenario**

ES020 - Professional uses: roller application or brushing, dipping and pouring and other processing without aerosol formation (inside)

### **Use of the substance/preparation**

Surface treatment of wood and other materials

### **Use**

SU22	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix
PROCh01	Other processing without aerosol formation
PROC13	Treatment of articles by dipping and pouring
PROC10	Roller application or brushing

## **Contributing exposure scenario controlling environmental exposure**

### **Use**

ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix

### **Physical form**

liquid

### **Maximum amount used per time or activity**

Emission days per site: <= 250

### **Other relevant operational conditions**

Use: Room temperature

Drying and through-curing takes place at ambient temperature or at higher temperatures.

Curing takes place through UV light exposure (only with UV light curing systems ).

Where possible recycling is preferred to disposal or incineration.

Do not allow to enter soil, waterways or waste water canal.

Trade name: glimtrex SIGNUM 1-Pack Lacquer mat 103003

Version: 34 / DE

Revision: 31.07.2020

Replaces Version: 33 / DE

Print date: 04.02.21

Dispose of rinse water in accordance with local and national regulations.

**Waste water**

Do not discharge into the drains/surface waters/groundwater.

**Exhaust air**

Keep container closed. Avoid release to the environment.

**Soil**

Floors should be impervious, resistant to liquids and easy to clean.

**Disposal recommendations for the product**

EWC waste code	080111 - waste paint and varnish containing organic solvents or other dangerous substances
	200127 - paint, inks, adhesives and resins containing dangerous substances

Where possible recycling is preferred to disposal or incineration.

Do not allow to enter drains or waterways.

**modified product**

EWC waste code	080115 - aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances
----------------	--

**Dried residues**

EWC waste code	080112 - waste lacquers and waste paint except those falling under 080111
----------------	---

**Disposal recommendations for packaging**

EWC waste code	150110 - packaging containing residues of or contaminated by dangerous substances
----------------	---

Germany: KBS system for sheet covering

Completely emptied packagings can be given for recycling.

**Contributing exposure scenario controlling worker exposure (professional)**

**Short title of the exposure scenario**

Substance number:CES040

**Use**

SU22	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
PROCh01	Other processing without aerosol formation
PROC10	Roller application or brushing
PROC13	Treatment of articles by dipping and pouring

**Physical form** liquid

**Maximum amount used per time or activity**

Duration of exposure	<=	8	h/d
Frequency of exposure	<=	220	d/a

**Other relevant operational conditions**

Use: Room temperature  
 Drying and through-curing takes place at ambient temperature or at higher temperatures.  
 Curing takes place through UV light exposure (only with UV light curing systems ).  
 Read attached instructions before use.

**Product substance and product safety related measures**

Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable



Trade name: glimtrex SIGNUM 1-Pack Lacquer mat 103003

Version: 34 / DE

Revision: 31.07.2020

Replaces Version: 33 / DE

Print date: 04.02.21

this should be achieved by the use of local exhaust ventilation and good general extraction. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

### Respiratory protection

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol. Recommended Filter type: Respiratory protection mask with combination filter A/P2

### Hand protection

Protective gloves complying with EN 374.

Glove material

Appropriate Material butyl-rubber

Material thickness  $\geq$  0,5

Breakthrough time  $\geq$  120

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

### Eye protection

Wear eye glasses with side protection according to EN 166.

### Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

## Exposure estimation and reference to its source

### Workers (professional)

SU	SU22
PROC	PROC10
Assessment method	inhalation, long-term - systemic
	Indoor use
Exposure assessment	36,9294 mg/m <sup>3</sup>
Exposure assessment (method)	ESIG GES tool
Risk characterisation ratio (RCR)	0,376831
Lead substance	2-butoxyethanol

### Workers (professional)

SU	SU22
PROC	PROC10
Assessment method	dermal, long-term - systemic
	Indoor use
Exposure assessment	5,4857 mg/kg/d
Exposure assessment (method)	ESIG GES tool
Risk characterisation ratio (RCR)	0,043887
Lead substance	2-butoxyethanol

### Workers (professional)

SU	SU22
----	------



Trade name: glimtrex SIGNUM 1-Pack Lacquer mat 103003

Version: 34 / DE

Revision: 31.07.2020

Replaces Version: 33 / DE

Print date: 04.02.21

PROC	PROC10
Assessment method	inhalation, long-term - systemic
	Outdoor use
Exposure assessment	51,7012 ppm
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,527563
Lead substance	2-butoxyethanol

**Workers (professional)**

SU	SU22
PROC	PROC10
Assessment method	dermal, long-term - systemic
	Outdoor use
Exposure assessment	3,2914 mg/kg/d
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,026331
Lead substance	2-butoxyethanol

**Workers (professional)**

SU	SU22
PROC	PROC11
Assessment method	inhalation, long-term - systemic
	Indoor use
Exposure assessment	62 mg/m <sup>3</sup>
Exposure assessment (method)	ESIG GES tool
Risk characterisation ratio (RCR)	0,632653
Lead substance	2-butoxyethanol

**Workers (professional)**

SU	SU22
PROC	PROC11
Assessment method	dermal, long-term - systemic
	Indoor use
Exposure assessment	12,8571 mg/kg/d
Exposure assessment (method)	ESIG GES tool
Risk characterisation ratio (RCR)	0,632653
Lead substance	2-butoxyethanol

**Workers (professional)**

SU	SU22
PROC	PROC11
Assessment method	inhalation, long-term - systemic
	Outdoor use
Exposure assessment	10 ppm
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,5
Lead substance	2-butoxyethanol

**Workers (professional)**

SU	SU22
PROC	PROC11
Assessment method	dermal, long-term - systemic
	Outdoor use
Exposure assessment	21 mg/kg/d
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,286

Trade name: glimtrex SIGNUM 1-Pack Lacquer mat 103003

Version: 34 / DE

Revision: 31.07.2020

Replaces Version: 33 / DE

Print date: 04.02.21

Lead substance 2-butoxyethanol  
**Workers (professional)**  
 SU SU22  
 PROC PROC13  
 Assessment method inhalation, long-term - systemic  
 Indoor use  
 Exposure assessment 49,2393 mg/m<sup>3</sup>  
 Exposure assessment (method) ESIG GES tool  
 Risk characterisation ratio (RCR) 0,502441  
 Lead substance 2-butoxyethanol

**Workers (professional)**  
 SU SU22  
 PROC PROC13  
 Assessment method dermal, long-term - systemic  
 Indoor use  
 Exposure assessment 2,7429 mg/kg/d  
 Exposure assessment (method) ESIG GES tool  
 Risk characterisation ratio (RCR) 0,021943  
 Lead substance 2-butoxyethanol

**Workers (professional)**  
 SU SU22  
 PROC PROC13  
 Assessment method inhalation, long-term - systemic  
 Outdoor use  
 Exposure assessment 7 ppm  
 Exposure assessment (method) ESIG GES tool  
 Risk characterisation ratio (RCR) 0,35  
 Lead substance 2-butoxyethanol

**Workers (professional)**  
 SU SU22  
 PROC PROC13  
 Assessment method dermal, long-term - systemic  
 Outdoor use  
 Exposure assessment 14 mg/kg/d  
 Exposure assessment (method) ESIG GES tool  
 Risk characterisation ratio (RCR) 0,183  
 Lead substance 2-butoxyethanol

**Workers (professional)**  
 SU SU22  
 PROC PROC10  
 Assessment method inhalation, long-term - local and systemic  
 Outdoor use  
 Exposure assessment 2,5 ppm  
 Risk characterisation ratio (RCR) 0,25  
 Lead substance 2-(2-butoxyethoxy)ethanol

**Workers (professional)**  
 SU SU22  
 PROC PROC10  
 Assessment method dermal, long-term - systemic  
 Outdoor use  
 Exposure assessment 2,74 mg/kg/d

Trade name: glimtrex SIGNUM 1-Pack Lacquer mat 103003

Version: 34 / DE

Revision: 31.07.2020

Replaces Version: 33 / DE

Print date: 04.02.21

Risk characterisation ratio (RCR)	0,137
Lead substance	2-(2-butoxyethoxy)ethanol
<b>Workers (professional)</b>	
SU	SU22
PROC	PROC10
Assessment method	inhalation, long-term - local and systemic Indoor use
Exposure assessment	1,25 ppm
Risk characterisation ratio (RCR)	0,125
Lead substance	2-(2-butoxyethoxy)ethanol
<b>Workers (professional)</b>	
SU	SU22
PROC	PROC10
Assessment method	dermal, long-term - systemic Indoor use
Exposure assessment	0,55 mg/kg/d
Risk characterisation ratio (RCR)	0,027
Lead substance	2-(2-butoxyethoxy)ethanol
<b>Workers (professional)</b>	
SU	SU22
PROC	PROC11
Assessment method	inhalation, long-term - local and systemic Indoor use
Exposure assessment	5 ppm
Risk characterisation ratio (RCR)	0,5
Lead substance	2-(2-butoxyethoxy)ethanol
<b>Workers (professional)</b>	
SU	SU22
PROC	PROC11
Assessment method	dermal, long-term - systemic Indoor use
Exposure assessment	2,14 mg/kg/d
Risk characterisation ratio (RCR)	0,107
Lead substance	2-(2-butoxyethoxy)ethanol
<b>Workers (professional)</b>	
SU	SU22
PROC	PROC11
Assessment method	inhalation, long-term - local and systemic Outdoor use
Exposure assessment	4,2 ppm
Risk characterisation ratio (RCR)	0,42
Lead substance	2-(2-butoxyethoxy)ethanol
<b>Workers (professional)</b>	
SU	SU22
PROC	PROC11
Assessment method	dermal, long-term - systemic Outdoor use
Exposure assessment	1,29 mg/kg/d
Risk characterisation ratio (RCR)	0,42
Lead substance	2-(2-butoxyethoxy)ethanol

Trade name: glimtrex SIGNUM 1-Pack Lacquer mat 103003

Version: 34 / DE

Revision: 31.07.2020

Replaces Version: 33 / DE

Print date: 04.02.21

**Workers (professional)**

SU	SU22
PROC	PROC13
Assessment method	inhalation, long-term - local and systemic
	Indoor use
Exposure assessment	2 ppm
Risk characterisation ratio (RCR)	0,2
Lead substance	2-(2-butoxyethoxy)ethanol

**Workers (professional)**

SU	SU22
PROC	PROC13
Assessment method	dermal, long-term - systemic
	Indoor use
Exposure assessment	0,69 mg/kg/d
Risk characterisation ratio (RCR)	0,034
Lead substance	2-(2-butoxyethoxy)ethanol

**Workers (professional)**

SU	SU22
PROC	PROC13
Assessment method	inhalation, long-term - local and systemic
	Outdoor use
Exposure assessment	4,2 ppm
Risk characterisation ratio (RCR)	0,42
Lead substance	2-(2-butoxyethoxy)ethanol

**Workers (professional)**

SU	SU22
PROC	PROC13
Assessment method	dermal, long-term - systemic
	Outdoor use
Exposure assessment	0,41 mg/kg/d
Risk characterisation ratio (RCR)	0,42
Lead substance	2-(2-butoxyethoxy)ethanol

**Information on estimated exposure and downstream-user guidance****Guidance for Downstream Users**

The downstream user can evaluate whether he operates within the conditions set in the exposure scenario on the basis of the information supplied. This evaluation can be conducted by an expert or using the risk assessment tools recommended by ECHA.

**Annex to the extended Safety Data Sheet (eSDS)****Short title of the exposure scenario**

ES040 - Private households (= general public = consumers): roller application or brushing, dipping and pouring, non industrial spraying and other processing without aerosol formation (inside)

**Use of the substance/preparation**

Surface treatment of wood and other materials

**Use**

SU21	Consumer uses: Private households (= general public = consumers)
ERC8a	Wide dispersive indoor use of processing aids in open systems

Trade name: glimtrex SIGNUM 1-Pack Lacquer mat 103003

Version: 34 / DE

Revision: 31.07.2020

Replaces Version: 33 / DE

Print date: 04.02.21

ERC8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix
PROCh01	Other processing without aerosol formation
PROC10	Roller application or brushing
PROC11	Non industrial spraying
PROC13	Treatment of articles by dipping and pouring

## Contributing exposure scenario controlling environmental exposure

### Use

ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix

### Physical form

liquid

### Maximum amount used per time or activity

Emission days per site: <= 20 d

### Other relevant operational conditions

Use: Room temperature  
 Adhere to the recommended processing temperature.  
 Volatile organic substances will volatilise into the atmospheric air inside.  
 Do not allow to enter soil, waterways or waste water canal.

### Waste water

Do not discharge into the drains/surface waters/groundwater.

### Exhaust air

No special measures required.

### Soil

Floors should be impervious, resistant to liquids and easy to clean. Protect floor with suitable covering plastic film / paper.

### Disposal recommendations for the product

EWC waste code	080111 - waste paint and varnish containing organic solvents or other dangerous substances 200127 - paint, inks, adhesives and resins containing dangerous substances
----------------	--

Where possible recycling is preferred to disposal or incineration.  
 Do not allow to enter drains or waterways.

### modified product

EWC waste code	080115 - aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances
----------------	--

### Dried residues

EWC waste code	080112 - waste lacquers and waste paint except those falling under 080111
----------------	---

### Disposal recommendations for packaging

EWC waste code	150110 - packaging containing residues of or contaminated by dangerous substances
----------------	---

Germany: KBS system for sheet covering  
 Completely emptied packagings can be given for recycling.

## Contributing exposure scenario controlling consumer exposure

### Use

Trade name: glimtrex SIGNUM 1-Pack Lacquer mat 103003

Version: 34 / DE

Revision: 31.07.2020

Replaces Version: 33 / DE

Print date: 04.02.21

SU21	Consumer uses: Private households (= general public = consumers)
PROCh01	Other processing without aerosol formation
PROC10	Roller application or brushing
PROC11	Non industrial spraying
PROC13	Treatment of articles by dipping and pouring

**Physical form** liquid**Maximum amount used per time or activity**

Duration of exposure	<=	4	h/d
Frequency of exposure	<=	20	d/a

**Other relevant operational conditions**

Use: Room temperature

Drying and through-curing takes place at ambient temperature or at higher temperatures.

Adhere to the recommended processing temperature.

Volatile organic substances will volatilise into the atmospheric air inside.

**Product substance and product safety related measures**

Keep out of reach of children. Wash hands before breaks and after work. Do not eat, drink or smoke when using this product.

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol.

Recommended Filter type: Respiratory protection mask with combination filter A/P2

Protective gloves complying with EN 374.

Glove material

Appropriate Material	butyl-rubber
----------------------	--------------

Material thickness	>=	0,5
--------------------	----	-----

Breakthrough time	>=	120
-------------------	----	-----

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Wear eye glasses with side protection according to EN 166.

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

**Information on estimated exposure and downstream-user guidance****Guidance for Downstream Users**

The downstream user can evaluate whether he operates within the conditions set in the exposure scenario on the basis of the information supplied. This evaluation can be conducted by an expert or using the risk assessment tools recommended by ECHA.