

Product Info sheet:
glimtrex[®] Degrayer



Product description

glimtrex[®] Degrayer suitable for the cleaning of greying exterior timber. It brings the natural colour of the wood back.

glimtrex[®] Degrayer is easy to apply, highly effective and very economical.

Application Instructions

- the surface should be clean and free from frost
- the wood humidity should not exceed 18%
- the humidity should be smaller than 60%
- wet the wood
- depending on the degree of pollution use glimtrex[®] Degrayer pure or diluted with water. The maximal mixing ratio is 1:5
- brush glimtrex[®] Degrayer into the wood in the direction of the grain.
- after an exposure time of 15 minutes you can brush the grey away with water.
- if necessary you can redo the procedure
- clean the floor with clear water
- after 24 hours the surface is recoatable
- use glimtrex[®] Outside Oil to guarantee a long-lasting protection

Yield

1 Litre for 10 - 50 m², depending on the degree of pollution (50 -100 ml/ m²).

Technical Information

Available in 1liter cans

Store cold but frost-free. The shelf life is 3 years in the closed original tin. Decant the open tins and hermetically seal them. Use them prompt.

Please look at the current safety data sheets. You will find them at www.glimtrex.de/downloads.

This information is purely advisory and is based on the best knowledge available through careful research. This information cannot be held as legally binding.