

Trade name: glimtrex Hardwax oil dark oak 102004

Version: 17 / DE Revision: 18.08.2023

Replaces Version: 16 / DE Print date: 19.10.23

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

glimtrex Hardwax oil dark oak 102004

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

## Use of the substance/preparation

Surface treatment of wood and other materials

## 1.3. Details of the supplier of the safety data sheet

#### Manufacturer

glimtrex GmbH Orkotten 68 48291 Telgte

Telephone no. +49 (0) 2504 88887-111 Fax no. +49 (0) 2504 88887-112 E-mail address info@glimtrex.de

## 1.4. Emergency telephone number

Germany: +49 (0) 30 30686700

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

#### Classification (Regulation (EC) No. 1272/2008)

This product is not classified hazardous in accordance with Regulation (EC) No 1272/2008.

## 2.2. Label elements

## Labelling according to regulation (EC) No 1272/2008

## Supplemental information

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH210 Safety data sheet available on request.

## **Further supplemental information**

Cleaning cloth soaked with the product can self ignite during packing up, therefore dry the cloth on a line or through spreading and dispose of after dry up.

#### 2.3. Other hazards

The product contains no PBT substances. The product contains no vPvB substances. This product does not contain a substance that has endocrine disrupting properties with respect to human. The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

## **SECTION 3: Composition/information on ingredients**

#### **Hazardous ingredients**

#### Naphtha (petroleum), hydrotreated heavy

CAS No. 64742-48-9 EINECS no. 919-857-5

Registration no. 01-2119463258-33

Concentration >= 25 < 50 %



Trade name: glimtrex Hardwax oil dark oak 102004

Version: 17 / DE Revision: 18.08.2023
Replaces Version: 16 / DE Print date: 19.10.23

Classification (Regulation (EC) No. 1272/2008)

Asp. Tox. 1 H304

Hydrocarbons, C11-C12, isoalkanes, <2% aromatics

EINECS no. 918-167-1

Registration no. 01-2119472146-39

Concentration >= 1 < 10 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3 H226 Asp. Tox. 1 H304 Aquatic Chronic 4 H413

alkanes, cycloalkanes, C11-14-iso-

EINECS no. 927-285-2

Registration no. 01-2119480162-45

Concentration >= 1 < 10 %

Classification (Regulation (EC) No. 1272/2008)

Asp. Tox. 1 H304

hydrocarbons, C11-C13, isoalkanes, <2% aromatics

EINECS no. 920-901-0

Registration no. 01-2119456810-40

Concentration >= 1 < 10 %

Classification (Regulation (EC) No. 1272/2008)

Asp. Tox. 1 H304

Solvent Red 122

CAS No. 12227-55-3

Concentration >= 0.1 < 0.3 %

Classification (Regulation (EC) No. 1272/2008)

Aquatic Acute 1 H400 Aquatic Chronic 1 H410

## Note

For explanation of abbreviations see section 16.

#### **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

#### **General information**

In all cases of doubt, or when symptoms persist, seek medical attention. If unconscious place in recovery position and seek medical advice. First aider: Pay attention to self-protection! Remove affected person from danger area, lay him down.

#### After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. Keep warm, calm and covered up. In all cases of doubt, or when symptoms persist, seek medical attention.

#### After skin contact

Wash off immediately with soap and water. Do NOT use solvents or thinners. Consult a doctor if skin irritation persists.

### After eye contact



Trade name: glimtrex Hardwax oil dark oak 102004

Version: 17 / DE Revision: 18.08.2023

Replaces Version: 16 / DE Print date: 19.10.23

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. Take medical treatment.

#### After ingestion

Do not induce vomiting. Take medical treatment.

## 4.2. Most important symptoms and effects, both acute and delayed

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. High concentration of vapours may cause irritation to eyes and respiratory system and produce narcotic effects.

# 4.3. Indication of any immediate medical attention and special treatment needed Hints for the physician / treatment

Treat symptomatically.

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

## Suitable extinguishing media

Recommended: alcohol resistant foam, CO2, powders, water spray/mist

#### Non suitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

## 5.2. Special hazards arising from the substance or mixture

Fire will produce dense black smoke. In a fire, hazardous decomposition products may be produced. Exposure to decomposition products may cause a health hazard. Vapours can form an explosive mixture with air.

#### 5.3. Advice for firefighters

## Special protective equipment for fire-fighting

In case of combustion evolution of dangerous gases possible. Use self-contained breathing apparatus.

#### Other information

Do not allow run-off from fire fighting to enter drains or water courses. Cool closed containers exposed to fire with water. Standard procedure for chemical fires.

#### **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Do not inhale vapours. Do not inhale gases. Do not inhale mist.

## **6.2. Environmental precautions**

Do not allow to enter drains or waterways. Do not allow to enter soil, waterways or waste water canal. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

#### 6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Do NOT use solvents or thinners. Send in suitable containers for recovery or disposal.

#### 6.4. Reference to other sections

Refer to protective measures listed in Sections 7 and 8.



Trade name: glimtrex Hardwax oil dark oak 102004

Version: 17 / DE Revision: 18.08.2023

Replaces Version: 16 / DE Print date: 19.10.23

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

#### Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Keep container tightly closed and dry in a cool, well-ventilated place. Use only with adequate ventilation/personal protection. Ensure adequate ventilation. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values. Avoid contact with skin and eyes. Avoid inhalation of vapour and spray mist. Do no eat, drink or smoke when using this product. Use personal protective clothing. For personal protection see Section 8.

## Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Vapours are heavier than air and may spread along floors. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Take measures to prevent the build up of electrostatic charge. Wear shoes with conductive soles. No sparking tools should be used. Fight fire with normal precautions from a reasonable distance. Do not process in the same cabin together with highly flammable material (e.g. CN lacquer) => fire hazard through self ignition! Cleaning cloth soaked with the product can self ignite during packing up, therefore dry the cloth on a line or through spreading and dispose of after dry up.

## 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Provide solvent-resistant and impermeable floor. Keep only in the original container in a cool, well ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

## Hints on storage assembly

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

### Storage classes

Storage class according to TRGS 510 10 Flammable liquids

#### Further information on storage conditions

Keep away from heat. Protect from sunlight. Keep away from sources of ignition - No smoking. Store in accordance with the particular national regulations.

#### 7.3. Specific end use(s)

See exposure scenario, if available.

## SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

#### **Exposure limit values**

## Naphtha (petroleum), hydrotreated heavy

List TRGS 900 (RCP)

Type Hydrocarbon mixture with group exposure limit according to RCP

method in TRGS 900 (DE)

Value 300 mg/m<sup>3</sup>

Status: 06/2023



Trade name: glimtrex Hardwax oil dark oak 102004

Version: 17 / DE Revision: 18.08.2023
Replaces Version: 16 / DE Print date: 19.10.23

#### alkanes, cycloalkanes, C11-14-iso-

List TRGS 900
Value 600 mg/m³
Maximum limit value: 2(II); Status: 01/2012

#### Hydrocarbons, C11-C12, isoalkanes, <2% aromatics

List TRGS 900
Value 600 mg/m³
Maximum limit value: 2(II); Status: 05/2013

## hydrocarbons, C11-C13, isoalkanes, <2% aromatics

List TRGS 900 (RCP)

Type Hydrocarbon mixture with group exposure limit according to RCP

method in TRGS 900 (DE)

Value 300 mg/m<sup>3</sup>

Status: 07/2022

## Occupational exposure limit for hydrocarbonate mixture (fraction) according to RCP method in chapter 2.9 TRGS 900

Value 300 mg/m<sup>3</sup>

#### Other information

-

#### 8.2. Exposure controls

#### **Exposure controls**

Users are advised to consider national Occupational Exposure Limits or other equivalent values. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

## Respiratory protection

Respiratory protection not applicable; Use breathing apparatus if exposed to vapours/dust/aerosol. Recommended Filter type: Respiratory protection mask with combination filter A/P2

#### Hand protection

Protective gloves complying with EN 374.

Glove material

Appropriate Material Nitrile rubber

Material thickness >= 0,4 mm Breakthrough time >= 30 min

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

#### Eye protection

Safety glasses with side-shields conforming to EN166

#### **Body protection**

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands



Trade name: glimtrex Hardwax oil dark oak 102004

Version: 17 / DE Revision: 18.08.2023
Replaces Version: 16 / DE Print date: 19.10.23

before breaks and after work.

## **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

Physical state liquid
Colour brown
Odour characteristic

**Melting point** 

Remarks not determined

Freezing point

Remarks not determined

Boiling point or initial boiling point and boiling range

Value 130 to 214 °C

Flammability
not determined

Upper and lower explosive limits

Remarks not determined

Flash point

Value > 60 °C

Ignition temperature

Remarks not determined

**Decomposition temperature** 

Remarks not determined

pH value

Remarks Not applicable

**Viscosity** 

Remarks not determined

Solubility(ies)

Remarks not determined

Partition coefficient n-octanol/water (log value)

Remarks not determined

Vapour pressure

Remarks not determined

Density and/or relative density

Value appr. 0,923 kg/l

Temperature 20 °C

Relative vapour density

Remarks not determined

**Particle characteristics** 

Remarks not determined

9.2. Other information

**Odour threshold** 



Trade name: glimtrex Hardwax oil dark oak 102004

Version: 17 / DE Revision: 18.08.2023
Replaces Version: 16 / DE Print date: 19.10.23

Remarks not determined

**Evaporation rate** 

Remarks not determined

Solubility in water

Remarks not determined

Efflux time

Value 40 to 60 s

Temperature 20 °C

Method DIN 53211 4 mm

**Explosive properties** 

evaluation not determined

**Oxidising properties** 

Remarks not determined

Non-volatile content

Value 43,3 %

Method calculated value

Other information

This information is not available.

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Stable under recommended storage and handling conditions (see section 7).

#### 10.2. Chemical stability

Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

To avoid thermal decomposition, do not overheat.

## 10.4. Conditions to avoid

Isolate from sources of heat, sparks and open flame.

#### 10.5. Incompatible materials

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

## 10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide, nitrous oxides (NOx), dense black smoke, No decomposition if used as prescribed.

## **SECTION 11: Toxicological information**

## 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity

Method Calculation method (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

Acute dermal toxicity

Method Calculation method (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.



Trade name: glimtrex Hardwax oil dark oak 102004

Version: 17 / DE Revision: 18.08.2023
Replaces Version: 16 / DE Print date: 19.10.23

#### Acute inhalational toxicity

Method Calculation method (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Method Calculation method (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Method Calculation method (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

Sensitization

Method Calculation method (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

Mutagenicity

Method Calculation method (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

Reproductive toxicity

Method Calculation method (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

Carcinogenicity

Method Calculation method (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

#### **Specific Target Organ Toxicity (STOT)**

Single exposure

Method Calculation method (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

Repeated exposure

Remarks Based on available data, the classification criteria are not met.

**Aspiration hazard** 

Based on available data, the classification criteria are not met.

#### **Aspiration hazard (Components)**

#### hydrocarbons, C11-C13, isoalkanes, <2% aromatics

Harmful: may cause lung damage if swallowed.

#### 11.2 Information on other hazards

#### **Endocrine disrupting properties with respect to humans**

The product does not contain a substance that has endocrine disrupting properties with respect to humans.

#### Other information

No toxicological data are available.

## **SECTION 12: Ecological information**

## 12.1. Toxicity

#### **General information**

For this subsection there is no ecotoxicological data available on the product as such.



Trade name: glimtrex Hardwax oil dark oak 102004

Version: 17 / DE Revision: 18.08.2023
Replaces Version: 16 / DE Print date: 19.10.23

#### **Daphnia toxicity (Components)**

#### Solvent Red 122

Species Daphnia magna (Water flea)

EC50 < 0,1 mg/l

Duration of exposure 48 h

## 12.2. Persistence and degradability

#### **General information**

For this subsection there is no ecotoxicological data available on the product as such.

#### 12.3. Bioaccumulative potential

#### **General information**

For this subsection there is no ecotoxicological data available on the product as such.

## Partition coefficient n-octanol/water (log value)

Remarks not determined

## 12.4. Mobility in soil

#### **General information**

For this subsection there is no ecotoxicological data available on the product as such.

#### Mobility in soil

no data available

#### 12.5. Results of PBT and vPvB assessment

#### **General information**

For this subsection there is no ecotoxicological data available on the product as such.

#### Results of PBT and vPvB assessment

The product contains no PBT substances

The product contains no vPvB substances.

#### 12.6 Endocrine disrupting properties

## **Endocrine disrupting properties with respect to the envrionment**

The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

#### 12.7. Other adverse effects

#### **General information**

For this subsection there is no ecotoxicological data available on the product as such.

#### General information / ecology

For this subsection there is no ecotoxicological data available on the product as such.

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

## Disposal recommendations for the product

EWC waste code 080111 - waste paint and varnish containing organic solvents

or other dangerous substances

EWC waste code 200127 - paint, inks, adhesives and resins containing

dangerous substances



Trade name: glimtrex Hardwax oil dark oak 102004

Version: 17 / DE Revision: 18.08.2023
Replaces Version: 16 / DE Print date: 19.10.23

Where possible recycling is preferred to disposal or incineration.

Do not allow to enter drains or waterways.

modified product

EWC waste code 080113 - sludges from paint or varnish containing organic

solvents or other dangerous substances

EWC waste code 080115 - aqueous sludges containing paint or varnish

containing organic solvents or other dangerous substances

**Dried residues** 

EWC waste code 080112 - waste lacquers and waste paint except those falling

under 080111

Disposal recommendations for packaging

EWC waste code 150110 - packaging containing residues of or contaminated

by dangerous substances

Germany: KBS system for sheet covering

Completely emptied packagings can be given for recycling.

**SECTION 14: Transport information** 

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
14.1. UN number	Not classified as dangerous in the meaning of transport regulations.	Not classified as dangerous in the meaning of sea and air transport regulations.	Not a dangerous substance as defined in the above regulations.

## **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Water Hazard Class (Germany)

Water Hazard Class WGK 2

(Germany)

Remarks Derivation of WGK according to Annex 1 No. 5.2 AwSV

VOC

VOC (EU) 56,2 % 519 g/l

#### 15.2. Chemical safety assessment

For this substance / mixture a chemical safety assessment was not carried out.

#### **SECTION 16: Other information**

#### Hazard statements listed in Chapter 3

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.
 H413 May cause long lasting harmful effects to aquatic life.

## **CLP** categories listed in Chapter 3

Aquatic Acute 1 Hazardous to the aquatic environment, acute, Category 1



Trade name: glimtrex Hardwax oil dark oak 102004

Version: 17 / DE Revision: 18.08.2023
Replaces Version: 16 / DE Print date: 19.10.23

Aquatic Chronic 1 Hazardous to the aquatic environment, chronic, Category 1
Aquatic Chronic 4 Hazardous to the aquatic environment, chronic, Category 4

Asp. Tox. 1 Aspiration hazard, Category 1 Flam. Liq. 3 Flammable liquid, Category 3

#### **Abbreviations**

RID - Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning theInternational Transport of Dangerous Goods by Rail)

IMDG - International Maritime Code for Dangerous Goods

IATA - International Air Transport Association

IATA-DGR - Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO-TI - Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS - Globally Harmonized System of Classification and Labelling of Chemicals

EINECS - European Inventory of Existing Commercial Chemical Substances

CAS - Chemical Abstracts Service (division of the American Chemical Society)

GefStoffV - Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

LOAEL - Lowest Observed Adverse Effect Level

LOEL - Lowest Observed Effect Level

NOAEL - No Observed Adverse Effect Level

NOEC - No Observed Effect Concentration

NOEL - No Observed Effect Level

OECD - Organisation for Econpmic Cooperation and Development

**VOC - Volatile Organic Compounds** 

Changes since the last version are highlighted in the margin (\*\*\*). This version replaces all previous versions.

This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification.

The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

The information contained herein is based on the present state of our knowledge and does therefore not guarantee certain properties.