

Trade name: glimtrex Hardwax-Oil gloss 101003

Version: 6 / DE

Revision: 29.03.2021

Replaces Version: 5 / DE

Print date: 21.06.21

## 1. Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

glimtrex Hardwax-Oil gloss 101003

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/preparation

Surface treatment of wood and other materials

### 1.3. Details of the supplier of the safety data sheet

#### Manufacturer

glimtrex GmbH

Orkotten 68

48291 Telgte

Telephone no.

+49 (0) 2504 88887-111

Fax no.

+49 (0) 2504 88887-112

E-mail address

info@glimtrex.de

### 1.4. Emergency telephone number

Germany: +49 (0) 30 30686700

## 2. Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification (Regulation (EC) No. 1272/2008)

This product is not classified hazardous in accordance with Regulation (EC) No 1272/2008.

### 2.2. Label elements

#### Labelling according to regulation (EC) No 1272/2008

#### Supplemental information

EUH066

Repeated exposure may cause skin dryness or cracking.

EUH210

Safety data sheet available on request.

#### Further supplemental information

Cleaning cloth soaked with the product can self ignite during packing up, therefore dry the cloth on a line or through spreading and dispose of after dry up.

### 2.3. Other hazards

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB) (if not listed in Section 3).

## 3. Composition/information on ingredients

### Hazardous ingredients

#### Naphtha (petroleum), hydrotreated heavy

CAS No.

64742-48-9

EINECS no.

265-150-3

Registration no.

01-2119457273-39

Concentration

&gt;= 25

&lt;

50

%

Classification (Regulation (EC) No. 1272/2008)

Trade name: glimtrex Hardwax-Oil gloss 101003

Version: 6 / DE

Revision: 29.03.2021

Replaces Version: 5 / DE

Print date: 21.06.21

Asp. Tox. 1 H304

**Hydrocarbons, C11-C12, isoalkanes, <2% aromatics**

EINECS no. 918-167-1  
 Registration no. 01-2119472146-39  
 Concentration  $\geq$  10 < 25 %  
 Classification (Regulation (EC) No. 1272/2008)  
 Flam. Liq. 3 H226  
 Asp. Tox. 1 H304  
 Aquatic Chronic 4 H413

**Hydrocarbons, C11-C13, isoalkanes, <2% aromatics**

CAS No. 246538-78-3  
 EINECS no. 920-901-0  
 Registration no. 01-2119456810-40  
 Concentration  $\geq$  1 < 10 %  
 Classification (Regulation (EC) No. 1272/2008)  
 Asp. Tox. 1 H304  
 EUH066

**Hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics**

EINECS no. 927-285-2  
 Registration no. 01-2119480162-45  
 Concentration  $\geq$  1 < 10 %  
 Classification (Regulation (EC) No. 1272/2008)  
 Asp. Tox. 1 H304

**Note**

For explanation of abbreviations see section 16.

This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57) (if not listed in Section 3).

**4. First aid measures****4.1. Description of first aid measures****General information**

In all cases of doubt, or when symptoms persist, seek medical attention. If unconscious place in recovery position and seek medical advice. First aider: Pay attention to self-protection! Remove affected person from danger area, lay him down.

**After inhalation**

In case of accident by inhalation: remove casualty to fresh air and keep at rest. Keep warm, calm and covered up. In all cases of doubt, or when symptoms persist, seek medical attention.

**After skin contact**

Wash off immediately with soap and water. Do NOT use solvents or thinners. Consult a doctor if skin irritation persists.

**After eye contact**

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. Take medical treatment.

**After ingestion**

Trade name: glimtrex Hardwax-Oil gloss 101003

Version: 6 / DE

Revision: 29.03.2021

Replaces Version: 5 / DE

Print date: 21.06.21

Do not induce vomiting. Take medical treatment.

#### **4.2. Most important symptoms and effects, both acute and delayed**

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. High concentration of vapours may cause irritation to eyes and respiratory system and produce narcotic effects.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

##### **Hints for the physician / treatment**

Treat symptomatically.

### **5. Firefighting measures**

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media**

Recommended: alcohol resistant foam, CO<sub>2</sub>, powders, water spray/mist

##### **Non suitable extinguishing media**

Do not use a solid water stream as it may scatter and spread fire.

#### **5.2. Special hazards arising from the substance or mixture**

Fire will produce dense black smoke. In a fire, hazardous decomposition products may be produced. Exposure to decomposition products may cause a health hazard. Vapours can form an explosive mixture with air.

#### **5.3. Advice for firefighters**

##### **Special protective equipment for fire-fighting**

In case of combustion evolution of dangerous gases possible. Use self-contained breathing apparatus.

##### **Other information**

Do not allow run-off from fire fighting to enter drains or water courses. Cool closed containers exposed to fire with water. Standard procedure for chemical fires.

### **6. Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Do not inhale vapours. Do not inhale gases. Do not inhale mist.

#### **6.2. Environmental precautions**

Do not allow to enter drains or waterways. Do not allow to enter soil, waterways or waste water canal. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

#### **6.3. Methods and material for containment and cleaning up**

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Do NOT use solvents or thinners. Send in suitable containers for recovery or disposal.

#### **6.4. Reference to other sections**

Refer to protective measures listed in Sections 7 and 8.

### **7. Handling and storage**

#### **7.1. Precautions for safe handling**

Trade name: glimtrex Hardwax-Oil gloss 101003

Version: 6 / DE

Revision: 29.03.2021

Replaces Version: 5 / DE

Print date: 21.06.21

### Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Keep container tightly closed and dry in a cool, well-ventilated place. Use only with adequate ventilation/personal protection. Ensure adequate ventilation. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values. Avoid contact with skin and eyes. Avoid inhalation of vapour and spray mist. Do not eat, drink or smoke when using this product. Use personal protective clothing. For personal protection see Section 8.

### Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Vapours are heavier than air and may spread along floors. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Take measures to prevent the build up of electrostatic charge. Wear shoes with conductive soles. No sparking tools should be used. Fight fire with normal precautions from a reasonable distance. Do not process in the same cabin together with highly flammable material (e.g. CN lacquer) => fire hazard through self ignition! Cleaning cloth soaked with the product can self ignite during packing up, therefore dry the cloth on a line or through spreading and dispose of after dry up.

## 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Provide solvent-resistant and impermeable floor. Keep only in the original container in a cool, well ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

### Hints on storage assembly

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

### Storage classes

Storage class according to TRGS 510      10                      Flammable liquids

### Further information on storage conditions

Keep away from heat. Protect from sunlight. Keep away from sources of ignition - No smoking. Store in accordance with the particular national regulations.

## 7.3. Specific end use(s)

See exposure scenario, if available.

## 8. Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limit values

##### Hydrocarbons, C11-C12, isoalkanes, <2% aromatics

List                                      TRGS 900  
Value                                      600                      mg/m<sup>3</sup>  
Maximum limit value: 2(II);      Status: 05/2013

##### Hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics

List                                      TRGS 900  
Value                                      300                      mg/m<sup>3</sup>  
Status: 05/2020

##### Hydrocarbons, C11-C13, isoalkanes, <2% aromatics

Trade name: glimtrex Hardwax-Oil gloss 101003

Version: 6 / DE

Revision: 29.03.2021

Replaces Version: 5 / DE

Print date: 21.06.21

List	TRGS 900
Value	600 mg/m <sup>3</sup>
Maximum limit value: 2(II); Status: 01/2012	

**Naphtha (petroleum), hydrotreated heavy**

Value	300 mg/m <sup>3</sup>
Status: 05/2020	

**Other information**

-

**8.2. Exposure controls****Exposure controls**

Users are advised to consider national Occupational Exposure Limits or other equivalent values. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

**Respiratory protection**

Respiratory protection not applicable; Use breathing apparatus if exposed to vapours/dust/aerosol. Recommended Filter type: Respiratory protection mask with combination filter A/P2

**Hand protection**

Protective gloves complying with EN 374.

Glove material

Appropriate Material	Nitrile rubber
----------------------	----------------

Material thickness	>=	0,4	mm
--------------------	----	-----	----

Breakthrough time	>=	30	min
-------------------	----	----	-----

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

**Eye protection**

Wear eye glasses with side protection according to EN 166.

**Body protection**

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

**9. Physical and chemical properties****9.1. Information on basic physical and chemical properties**

<b>Form</b>	liquid
<b>Colour</b>	colourless
<b>Odour</b>	characteristic

**Odour threshold**

Remarks	not determined
---------	----------------

**Melting point**

Trade name: glimtrex Hardwax-Oil gloss 101003

Version: 6 / DE

Revision: 29.03.2021

Replaces Version: 5 / DE

Print date: 21.06.21

Remarks not determined

**Freezing point**

Remarks not determined

**Initial boiling point and boiling range**

Value 100 to 214 °C

**Flash point**

Value > 60 °C

**Evaporation rate**

Remarks not determined

**Flammability (solid, gas)**

not determined

**Upper/lower flammability or explosive limits**

Remarks not determined

**Vapour pressure**

Remarks not determined

**Vapour density**

Remarks not determined

**Density**

Value appr. 0,873 kg/l  
Temperature 20 °C

**Solubility in water**

Remarks not determined

**Solubility(ies)**

Remarks not determined

**Partition coefficient: n-octanol/water**

Remarks not determined

**Ignition temperature**

Remarks not determined

**Decomposition temperature**

Remarks not determined

**Viscosity**

Remarks not determined

**Efflux time**

Value 42 to 55 s  
Temperature 20 °C  
Method DIN 53211 4 mm

**Explosive properties**

evaluation not determined

**Oxidising properties**

Remarks not determined

**9.2. Other information**

**Non-volatile content**

Trade name: glimtrex Hardwax-Oil gloss 101003

Version: 6 / DE

Revision: 29.03.2021

Replaces Version: 5 / DE

Print date: 21.06.21

Value	43,5	%
Method	calculated value	

**Other information**

This information is not available.

**10. Stability and reactivity****10.1. Reactivity**

Stable under recommended storage and handling conditions (see section 7).

**10.2. Chemical stability**

Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

To avoid thermal decomposition, do not overheat.

**10.4. Conditions to avoid**

Isolate from sources of heat, sparks and open flame.

**10.5. Incompatible materials**

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

**10.6. Hazardous decomposition products**

Carbon monoxide and carbon dioxide, nitrous oxides (NOx), dense black smoke, No decomposition if used as prescribed.

**11. Toxicological information****11.1. Information on toxicological effects****Acute oral toxicity**

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

**Acute dermal toxicity**

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

**Acute inhalational toxicity**

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

**Skin corrosion/irritation**

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

**Serious eye damage/irritation**

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

**Sensitization**

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

**Mutagenicity**

Method	Calculation method (Regulation (EC) No. 1272/2008)
--------	--

Trade name: glimtrex Hardwax-Oil gloss 101003

Version: 6 / DE

Revision: 29.03.2021

Replaces Version: 5 / DE

Print date: 21.06.21

Remarks Based on available data, the classification criteria are not met.

**Reproductive toxicity**

Method Calculation method (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

**Carcinogenicity**

Method Calculation method (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity (STOT)****Single exposure**

Method Calculation method (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

**Repeated exposure**

Remarks Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Other information**

No toxicological data are available.

**12. Ecological information****12.1. Toxicity****General information**

For this subsection there is no ecotoxicological data available on the product as such.

**Fish toxicity (Components)****Hydrocarbons, C11-C13, isoalkanes, <2% aromatics**

Species	Fish		
LC50/EC50/IC50/LL50/EL5	>	100	mg/l
0			
Duration of exposure	=	96	h

**Daphnia toxicity (Components)****Hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics**

Species	Daphnia magna (Water flea)		
EC50	>	1000	mg/l
Duration of exposure		48	h

**12.2. Persistence and degradability****General information**

For this subsection there is no ecotoxicological data available on the product as such.

**Biodegradability (Components)****Hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics**

evaluation Not readily biodegradable.

**Hydrocarbons, C11-C13, isoalkanes, <2% aromatics**

evaluation Not readily biodegradable.

**12.3. Bioaccumulative potential****General information**



Trade name: glimtrex Hardwax-Oil gloss 101003

Version: 6 / DE

Revision: 29.03.2021

Replaces Version: 5 / DE

Print date: 21.06.21

For this subsection there is no ecotoxicological data available on the product as such.

**Partition coefficient: n-octanol/water**

Remarks not determined

**12.4. Mobility in soil**

**General information**

For this subsection there is no ecotoxicological data available on the product as such.

**Mobility in soil**

no data available

**12.5. Results of PBT and vPvB assessment**

**General information**

For this subsection there is no ecotoxicological data available on the product as such.

**12.6. Other adverse effects**

**General information**

For this subsection there is no ecotoxicological data available on the product as such.

**General information / ecology**

For this subsection there is no ecotoxicological data available on the product as such.

**13. Disposal considerations**

**13.1. Waste treatment methods**

**Disposal recommendations for the product**

EWC waste code	080111 - waste paint and varnish containing organic solvents or other dangerous substances
EWC waste code	200127 - paint, inks, adhesives and resins containing dangerous substances

Where possible recycling is preferred to disposal or incineration.  
Do not allow to enter drains or waterways.

**modified product**

EWC waste code	080113 - sludges from paint or varnish containing organic solvents or other dangerous substances
EWC waste code	080115 - aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances

**Dried residues**

EWC waste code	080112 - waste lacquers and waste paint except those falling under 080111
----------------	---

**Disposal recommendations for packaging**

EWC waste code	150110 - packaging containing residues of or contaminated by dangerous substances
----------------	---

Germany: KBS system for sheet covering  
Completely emptied packagings can be given for recycling.

**14. Transport information**

Trade name: glimtrex Hardwax-Oil gloss 101003

Version: 6 / DE

Revision: 29.03.2021

Replaces Version: 5 / DE

Print date: 21.06.21

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
<b>14.1. UN number</b>	Not classified as dangerous in the meaning of transport regulations.	Not classified as dangerous in the meaning of sea and air transport regulations.	Not a dangerous substance as defined in the above regulations.

## 15. Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Water Hazard Class (Germany)

Water Hazard Class (Germany)      WGK 2

Remarks      Derivation of WGK according to Annex 1 No. 5.2 AwSV

#### VOC

VOC (EU)      56,4      %      492      g/l

#### Other information

All components are contained in the TSCA inventory or exempted.

### 15.2. Chemical safety assessment

For this substance / mixture a chemical safety assessment was not carried out.

## 16. Other information

#### Hazard statements listed in Chapter 3

EUH066      Repeated exposure may cause skin dryness or cracking.  
 H226      Flammable liquid and vapour.  
 H304      May be fatal if swallowed and enters airways.  
 H413      May cause long lasting harmful effects to aquatic life.

#### CLP categories listed in Chapter 3

Aquatic Chronic 4      Hazardous to the aquatic environment, chronic, Category 4  
 Asp. Tox. 1      Aspiration hazard, Category 1  
 Flam. Liq. 3      Flammable liquid, Category 3

#### Abbreviations

ADR - Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 RID - Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
 IMDG - International Maritime Code for Dangerous Goods  
 IATA - International Air Transport Association  
 IATA-DGR - Dangerous Goods Regulations by the "International Air Transport Association" (IATA)  
 ICAO-TI - Technical Instructions by the "International Civil Aviation Organization" (ICAO)  
 GHS - Globally Harmonized System of Classification and Labelling of Chemicals  
 EINECS - European Inventory of Existing Commercial Chemical Substances  
 CAS - Chemical Abstracts Service (division of the American Chemical Society)  
 GefStoffV - Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)  
 LOAEL - Lowest Observed Adverse Effect Level  
 LOEL - Lowest Observed Effect Level

Trade name: glimtrex Hardwax-Oil gloss 101003

Version: 6 / DE

Revision: 29.03.2021

Replaces Version: 5 / DE

Print date: 21.06.21

NOAEL - No Observed Adverse Effect Level

NOEC - No Observed Effect Concentration

NOEL - No Observed Effect Level

OECD - Organisation for Economic Cooperation and Development

VOC - Volatile Organic Compounds

Changes since the last version are highlighted in the margin (\*\*). This version replaces all previous versions.

This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification.

The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

The information contained herein is based on the present state of our knowledge and does therefore not guarantee certain properties.