

Product info sheet:
glimtrex[®] SIGNUM
Hydro foundation



Product description

Hydro foundation is made for the pre-treatment of wood when using the SIGNUM-Lacquer-System:

Characteristics

- free of starting points,
- elastic
- quick drying
- strong penetration
- minimizes the risk of gluing on the sides
- low raising of wood grain

Pretreatment

- Sand surfaces with 80-120 grit sandpaper. (we recommend our glimtrex[®] Multi whole pad K120)
- Remove any dirt or sanding dust.
- to minimize the risk of gluing of the sides, roll glimtrex[®] SIGNUM Hydro foundation on the surface.

Surface treatment

- before using glimtrex[®] SIGNUM Hydro foundation bring it to it's processing temperature
- shake it
- Before your pour the product out wait 2 - 5 minutes and use a lacquer sieve
- Don't pour the product on the floor. Instead use a lacquer bucket
- Apply 100- 125 g/m² minimum per coat
- Apply the lacquer with the glimtrex[®] SIGNUM Hydro foundation with a Lacquerroller
- drying time is 2-3 hours at 20C and 50% rel. humidity
- afterwards a coat of glimtrex[®] SIGNUM 1K or 2K Lacquer needs to be applied. Without intermediate sanding!



Regular cleaning

- Remove loose dust with a broom or vacuum cleaner
- For regular cleaning please use **25 - 50 ml glimtrex® Floor-Care for 5 litre Water.**
- For a high pollution adjust the amount of Floor care in the water

Technical information

Available in 5 liter tins.

The shelf life is 26 weeks in the closed original tin. Make sure to stir the tin thoroughly before using. A skin may form on the surface of the product, please remove before stirring.

Please look at the current safety data sheets. You will find them at www.glimtrex.de/downloads.

This information is purely advisory and is based on the best knowledge available through careful research. This information cannot be held as legally binding.

More over we refer to the general terms and conditions.