

Professional maintenance-instruction for oiled and hardwaxed wooden floors



Regular cleaning

- For daily dirt and dust a broom or mop is sufficient. If you use a vacuum cleaner please use a **brush attachment** to avoid scratches.
- For a high pollution please use a damp cloth with **glimtrex® Floor-Care** in water.
- Our water additive is ph- neutral, solvent-free and free from colorants. It is made on a base of biodegradable tensides and natural wax from the carnauba palm
- For regular cleaning please use **25 - 50 ml glimtrex® Floor-Care for 5 litre Water**.
- For very high pollution we recommend glimtrex® Remover in combination with glimtrex® Intensive-Care.
- Please make sure only a **damp mop** is used so that after the cleaning no water is left on the floor.

Refreshing possibility 1 1: Less work short drytimes

- Dilute glimtrex® Remover according to the degree of pollution.
- For the basic cleaning we recommend 1 litre glimtrex® Remover to 5 litre Water. This mixture is sufficient for about 60 m².
- For a very high pollution you can adjust the mixing ratio to 1:1.
- Mop the floor with a damp mop and leave the glimtrex® Remover for 5 minutes on the floor so it can work into the floor.
- Please make sure that glimtrex® Remover is distributed evenly and on the entire floor.
- After, use a mop with clear water to remove the dirt and possible Remover remains.
- Before using glimtrex® Intensive-Care the floor has to be dry.
- **Consider that you have to use a separate and clean mop for the glimtrex® Intensive-Care.**
- Apply glimtrex® Intensive-Care undiluted with a normal mop.
- Spread out the glimtrex® Intensive-Care along the grain of the wood.
- Make sure glimtrex® Intensive-Care is distributed evenly and over the entire floor.
- After drying for 2- 3 hours at room temperature of 20 degrees you can use the floor again.
- If the floor is heavily used regularly we recommend to do the refreshing multiple times a year.



Refreshing possibility 2: intensiverer Auffrischungsgrad

- Use glimtrex® Remover in ratio 1:1.
 - For heavy dirt you can use glimtrex® Remover undiluted.
 - Use a buffing-machine with a white or brown pad to buff in glimtrex® Remover on the whole area.
 - Please make sure that glimtrex® Remover is distributed evenly and on the entire floor.
 - After, use a mop with clear water to remove the dirt and possible Remover remains.
 - Before using glimtrex® Wax-Polish the floor has to be completely dry.
 - Lightly and evenly run in glimtrex® Wax-Polish across the entire floor with a lint-free cotton cloth and immediately remove any excess amounts with the cloth
 - Using a single disc machine with a white pad will achieve even better results
 - The floor can be used again after around 8 hours
 - Please only use glimtrex® Wax-Polish across the entire surface
 - For partial retouching please use our glimtrex® Hardwax-Oil
- **Oil-saturated cotton cloths pose a risk of spontaneous combustion due to heat buildup; therefore it is advised to spread them out and allow them to air dry before disposal.**