

Product info sheet:
SIGNUM Grout Solution

Product description

SIGNUM Grout Solution is made to join tiles up to 2 mm and to fill smaller imperfections on the wooden surface

Characteristics

- water based
- high filling power
- quick drying
- low odour
- environmentally friendly
- good sanding characteristics
- easy to apply

Surface treatment

Please shake glimtrex® SIGNUM **Grout Solution** before using. Mix it with fine saw dust so it is ready to use. Saw dust from edge strips are perfectly suitable. The finer the dust, the better the joints are connected.

Smooth the entire parquets surface. Prefill wide joints or smooth them 2 times.

Clean the devices with water. If the Saw dust mixture is too tough please use glimtrex® SIGNUM Grout Solution to dilute the mixture. Don't use water!

The drying is approximately 1 hour.

Intermediate Sanding: Roller Grinding Machine: Korn 100 – 120

Final sanding with single-disc sanding machine: Korn / Gitter 120 - 150. Dust after.

Make sure no grout remains on the surface. Risk of staining!

Dust the sanded surface before further processing.

Technical information

Available in 5 liter tins.

The shelf life is 26 weeks in the closed original tin. Make sure to stir the tin thoroughly before using. A skin may form on the surface of the product, please remove before stirring.

Please look at the current safety data sheets. You will find them at www.glimtrex.de/downloads.

This information is purely advisory and is based on the best knowledge available through careful research. This information cannot be held as legally binding.

More over we refer to the general terms and conditions.