



Product info sheet: **glimtrex[®] Hardener**

Product description

glimtrex[®] Hardener is an additive for glimtrex[®] Hardwax-Oil which reduces drying times and increases surface strength.

Characteristics

- Only to be used in conjunction with glimtrex[®] Hardwax-Oil
- Suitable for all wood and cork surfaces
- Improves surface durability and lifespan
- Easy to use
- Helps to reduce drying time
- Creates non-slip surfaces (R10, as specified for public buildings)
- Also achieves excellent results on exotic woods

Application instructions

- Mix in the glimtrex[®] Hardwax-Oil with 5 % glimtrex[®] Hardener
- Make sure that the Hardener and the Hardwax-Oil are well mixed
- Evenly roll on the material
- Before applying the second layer it is imperative that an interim polish be carried out
- Application time is around 1 hour, and it is recommended to not prepare more material than can be applied within that timeframe

Technical information

Available in 0.125 and 0.5 liter tins.

Oil-saturated cotton cloths pose a risk of spontaneous combustion due to heat buildup; therefore it is advised to spread them out and allow them to air dry before disposal.

The shelf life is 12 months in the closed original tin. Make sure to stir the tin thoroughly before using. A skin may form on the surface of the product, please remove before stirring.

Please look at the current safety data sheets. You will find them at www.glimtrex.de/downloads.

This information is purely advisory and is based on the best knowledge available through careful research. This information cannot be held as legally binding.