Product info sheet:

glimtrex® Wood-Opaque-Colour



Product description

glimtrex [®] Wood-Opaque-Colour is an open pored and coating finish for exteriors. It has a high resistance against weathering and is suitable for the restoration of old, open- pored finished of weathered wood.

Characteristics

- based of natural renewable raw materials
- DIN EN 71-3: Security of children's toys
- · protects for turning blue or mould
- water resistant
- keeps the wood from greying
- high and long lasting weathering protection
- UV- Protection
- easy to apply

Application instructions

- · stir the product before using
- old colour and lacquer remains have to be removed
- for an open- pored coating clean the wood thoroughly
- processing temperature (including drying) should be higher than + 8 °C. The wood humidity shout not exceed 18% and the humidity should be below 60%.
- apply glimtrex[®] Wood-Opaque-Colour thin and evenly with a whitewash brush, a brush or a roller drying time is approximately 12-24 hours (normal climate 23° and relative humidity of 50%)
- dust-dry after 6 hours
- you can apply a second coat after 12-24 hours (one coat should be enough for renewing)

Tel.:

Fax:

E-Mail:

Internet:

+49 (0)2504-88887-111

+49 (0)2504-88887-112

info@glimtrex.de

www.glimtrex.de



Yield

1 Litre for 25 m² per coat. Depending on the type of wood or the wooden surface (freshly sawn or planed wood). If the surface is ripped the yield might double.

Technical information

Available in 0.75 litre and 2.5 litre tins.

Colours: Transparent, white, ivory, sun-yellow, spruce-yellow, nordish-red, zeder, firered, pepple grey, light grey, street grey, stone grey, black grey, dusty blue, turkise blue, labrador, royal blue, fir sprigs, middle blue, dark blue, anahacitre grey, grey beige.

Oil-saturated cotton cloths pose a risk of spontaneous combustion due to heat build-up; therefore it is advised to spread them out and allow them to air dry before disposal.

The shelf life is 12 month in the closed original tin. Make sure to stir the tin thoroughly before using. A skin may from on the surface of the product, please remove before stirring.

Please look at the current safety data sheets. You will find them at www.glimtrex.de/downloads.

This information is purely advisory and is based on the best knowledge available through careful research. This information cannot be held as legally binding.

Tel.:

Fax:

E-Mail:

Internet:

+49 (0)2504-88887-111

+49 (0)2504-88887-112

info@glimtrex.de www.glimtrex.de